

-25°C Freezer



Technical Parameters

Model	BDF-25V268	BDF-25V328	BDF-25V270	BDF-25V350
External Size(W*D*H) mm	673*676*1630	673*676*1886	690*744*1631	690*744*1885
Capacity	268L	328L	270L	350L
Type	Vertical			
Temp. Range	-10°C~-25°C			
Temp. Accuracy	0.1°C			
Control System	Microprocessor Control & LED Display			
Alarm	High and low temperature; sensor failure; Door ajar alarm; Thermostat alarm		High or low temperature alarm, power outage alarm,Thermostat alarm,Door switch alarm	
Refrigeration Type	Direct Refrigeration			
Refrigerant	R290, CFC free			
Compressor	International famous compressor			
Condenser & Evaporator	Wire tube condenser; Coil type evaporator			
Construction	Structure	Unibody Design & Mono-assembly foaming (Rigid polyurethane insulation material)		
	Internal Material	Spraying steel plate		SUS304
	External Material	Spraying steel plate		Cold-rolled steel coated with bacterial powder
Shelve	3pcs	4pcs	3pcs	4pcs
Consumption	180W	180W	290W	305W
Power Supply	AC220V±10%, 50/60Hz; 110V±10%,60Hz		220V±10%, 50Hz	
Package Size(W*D*H) mm	760*760*1750	750*760*2030	810*860*1820	810*860*2100
Gross Weight	114kg	125kg	155kg	170kg

-25°C Freezer



Technical Parameters

Model	BDF-25V100	BDF-25V936	
External Size(W*D*H) mm	540*540*880	1304*1000*2017	
Internal Size(W*D*H) mm	410*410*670	1000*700*1335	
Capacity	100L	936L	
Type	Vertical		
Temp. Range	-10°C~-25°C		
Temp. Accuracy	0.1°C		
Control System	Microprocessor control, LED Digital Display		
Audible and Visual Alarm	High and low temperature alarm, sensor failure alarm, power failure alarm, door open alarm, etc.	High and low temperature alarm, sensor failure alarm, thermostat failure alarm, power failure alarm, door open alarm, ambient temperature alarm, condenser failure alarm, filter inspection alarm, abnormal voltage alarm, low battery alarm.	
Alarm Method	Sound beeps and lights flash		
Refrigeration type	Direct refrigeration		
Refrigerant	R600a	R404A	
Construction	Foam Layer Thickness	65mm	150mm
	Internal Material	HIPS	304 stainless steel
	External Material	Sprayed steel plate	
Consumption	150W	1000W	
Power Supply	AC220V±10%, 50/60Hz	AC110V/220V±10%, 50/60Hz	
Package Size (W*D*H) mm	610*625*950	1360*1135*2170	
Gross Weight	43kg	421kg	